Air Remote TTL-C Integrates camera and flash



Off-camera TTL control for Profoto AirTTL flashes

Place the Air Remote TTL-C on your camera hot shoe and merge your camera with your Profoto AirTTL flash. Then point and shoot and let the flash automatically adjust the light output for a perfect exposure. It could not be easier.

Remote control for Profoto Air flashes

With the Air Remote TTL-C you can remote control multiple Profoto Air flashes directly from your camera. You can control an endless number of lights in up to 3 groups from up to 300 m (1.000 ft) away!

Fast and reliable flash sync

Air is one of the most reliable wireless systems available to sync your flashes with your camera. It is also fast enough to provide a perfect flash sync down to the fastest X-sync speed of your camera. If you are using Profoto Air flashes no external receiver is required. If other flashes are used, connect an optional Air Remote or Air Sync transceiver to your flash and set it as receiver.

A wireless system with a wide range of options

Air Remote TTL-C is an integrated part of a wide range of Air products. The range of products within the system comprises camera transceivers, accessory cables and software solutions. All designed to offer a better wireless solution for professional photographers. More info is available at profoto.com.



Technical information



Features Air Remote TTL-C

- Canon hotshoe mount.
- Off-Camera TTL control for Profoto AirTTL flashes.
- Remote control for Profoto Air flashes.
- Compatible with Air Sync and Air Remote transceivers.
- Wireless range up to 300 m (1.000 ft).
- Short transmission delay. Supports the fastest X-sync speed on most Canon cameras.
- 2.4 Ghz operation approved worldwide.
- 8 digital channels.
- Controls up to 3 groups of lights on each channel.
- Very easy operation.
- Compact design that integrates with the camera.

C-	ecif		410	
3D	ecit	ıca	LIO	ns

Product number

901039 Air Remote TTL-C

1 x Air Remote TTL-C incl. batteries 1 x USB 2.0 cable 1 x wrist-strap

1x accessory pouch

Information

Please note

Find the latest firmware upgrades and a complete list of Canon EOS camera models that are approved with Air Remote TTL-C in the latest release notes on profoto.com/myprofoto

Size

77 x 60 x 40 mm (3.0 x 2.3 x 1.6 in)

Weight

90 g (3.2 oz) incl. batteries

Short specifications

Frequency band: 2.4 GHz No. of channels: 8 (1-8)

Wireless range: Up to 300 m (1000 ft) Connections: Canon hot shoe

Power input: 2 x AAA Alkaline Battery life: Up to 30 hours